MAX SWIPES





www.graffitisolutions.com 1.800.891.0091

GRAFFITI REMOVER TOWELETTES

GENERAL DESCRIPTION

MAX SWIPES Graffiti Remover is one of five "Graffiti Max" products, each custom formulated for specific graffiti removal needs.

MAX SWIPES Towelettes is the right choice for the job if it is a "smooth and durable surface" such as the following.

RECOMMENDED FOR REMOVAL ON

METALS: Stainless steel, galvanized, aluminum, brass, copper, anodized aluminum and zinc.

GLASS: All types - glazed tiles, ceramic, porcelain, polished stone, such as marble or granite.

DURABLE PAINTED: Factory applied baked on paint such as auto, truck, bus, equipment enamels, utility boxes, railcars or similar.

DURABLE PLASTICS: Plexiglas, Lexan, fiberglass, polyethylene or polypropylene portable toilets or bathroom partitions, laminated wood. Vinyl seats on buses, trains, subway cars and restaurant booths.

PRODUCT FEATURES AND BENEFITS

- **Thick Pre-moistened** towelettes for convenience.
- Fast removals just a few minutes for most uses.
- Low odor with minimal or no ventilation requirement for added safety, indoor or out.
- Nonflammable, noncombustible, for added safety in use.

SAFETY INSTRUCTIONS FOR USE

 Use chemical resistant gloves for repeated or extended use.

GENERAL INSTRUCTIONS FOR USE

- Should be tested first in an inconspicuous area for effect on any painted or plastic surface for effect.
- Remove MAX SWIPES Towelettes from center thru opening. Pull at 90° angle to tear at perforation.
- Ball towelette up and wipe over affected area. For paint, you may have to turn the towelette and repeat process until graffiti is removed.
- After area is cleaned, you may wipe surface with a clean damp cloth to stop remaining cleaning action.

SPEC'S - GENERAL PROPERTIES

CONSISTENCY

Pre-moistened polypropylene towelette.

COVERAGE

Non-porous surfaces 1-2 square feet per towelette.

TEMPERATURE USAGE

Not limited, will work slower at cold temperatures.

STORAGE

Stores between 40°F and 130°F. DO NOT FREEZE. If frozen, thaw. Keep out of the reach of children.

FLAMMABILITY

Nonflammable, noncombustible. Flash point over 200°F.

V.O.C.S

.2 lbs/gallon, 25 grams/liter. H.A.P.S. - none.

BIODEGRADABLE

Yes

VOLATILITY

Very low rate of evaporation.

SHIPPING

Not regulated, D.O.T. Proper shipping name: Cleaning Compound N.O.S., Class 55.

EFFECTIVE ON THE FOLLOWING

Spray paint graffiti, marker, pen, ink, crayon, shoe polish, lipstick, pencil, and most other graffiti marks or stains.

OTHER USES

MAX SWIPES Graffiti Remover Towelette removes road tar, asphalt, wax, tree sap and many other difficult to remove graffiti from durable smooth surfaces.

NOTE: If removing graffiti or shadows from porous surfaces such as brick, cement, grout, etc. We recommend using our **ELEPHANT SNOT**[®] Graffiti Remover or **SHADOW MAX** for shadow removals.

For larger jobs use **SMOOTH MAX**Graffiti Remover on all types of metals,
"durable" baked-on painted surfaces such
as autos, buses, trucks, and other factory
applied paints or fiberglass.